ALTRA10x

The Next Generation of the Formerly Known Agua-Pipe®



DELIVERING RESILIENCE

Our next-generation technology protects and renews your current water infrastructure from the inside with minimal disruption to your communities.

BENEFITS

1,370 miles / 2,200 km of water technology installed so far has proven to:

YEARS OF SERVICE LIFE ADDED TO WATER DISTRIBUTION SYSTEMS

- Structural, class IV, high resiliency against severe soil movements like frost heave, flooding, landslides, subsidence, nearby excavations, and earthquakes;
- Increased pressure and flow capacity;
- Added corrosion resistance;
- Regained full structural integrity;
- 100 year life expectancy.

ENVIRONMENTAL BENEFITS

- Elimination of risk of future water main breaks;
- Reduction of 55M m³ of drinking water leaks;
- Most environmentally friendly option with less GHG.

INSTALLATION BENEFITS

- Enable work in difficult to access, ecologically sensitive or high density area (e.g., highways, etc.);
- Quick installation with minimal disruption for the community;
- Little excavation and noise leading to fewer complains from neighboring residents;
- No disturbance to adjacent infrastructures:
- Line through bends and future service taps easily performed;
- No future maintenance required;
- Replacing lead services can be done simultaneously.

ECONOMIC CONSIDERATIONS

- Most cost effective water main infrastructure replacement methods;
- Reduction in treatment and pumping costs.

TEAM OF WATER EXPERTS

PUTTING OUR EXPERIENCE TO WORK FOR YOU

We have a proven track record of successful installation across North America, and we have developed deep expertise and advanced the state of the art with our trenchless technologies.



Benoit Côté
President
SANEXEN Water
bcote@
sanexen.com

Martin Bureau VP Innovation, SANEXEN mbureau@ sanexen.com Michael Davison General Manager, ALTRA mdavidson@ sapexen.com Gilles Gagnon
Director,
Research and
Development,
ALTRA
ggagnon@
sanexen.com

Didier Girard
Project Director,
SANEXEN
dgirard@

OUR FIELD-PROVEN EXPERTISE

- Acton (MA)
- Baltimore County (MD)
- Boston (MA)
- Burlington (VT)
- Cleveland (OH).
- Detroit (MI)
- Foxborough (MA)
- Francis Scott Key Bridge (MDTA)
- Harrisburg (PA)

- Jersey City (NJ)
- Livingston (NJ)
- Los Angeles (CA)
- Montreal (QC)
- Monroe County (NY)
- Naperville (IL)
- NewYork City (NY)
- North Penn Water (PA)
- Omaha (NE)
- Perkasie (PA)

- The Port Authority of NYNJ (Holland Tunnel)
- Providence (RI)
- Suez Water (NJ)
- Toronto (ON)
- Washington (DC)
- Webster (MA)
- Woodbridge (NJ)

and many more.

TECHNICAL SPECIFICATIONS

DIAMETER

ALTRA 10X: 4-12 inches (100-300 mm)

INSTALLATION LENGTH

Up to 1,000 feet (300 m) between access pits

INSTALLATION METHOD

Pulled-in-Place Pipe (PIPP)

OPERATING PRESSURE

Tested at greater than 150 psi

ALTRA10X LINER

Circular woven textile yarn jackets produced in our manufacturing facility and proprietary thermosetting resin

HAZEN-WILLIAMS COEFFICIENT

Greater than 120

LINER LIFESPAN

More than 100 year life expectancy

CLASS IV STAND-ALONE STRUCTURAL LINER

- Regained pressure and flow capacity
- Corrosion resistance
- Regained structural capacity
- Proven not to break upon hostpipe failure.

The ALTRA10X Structural Liners offer many advantages, such as when:

- Complete access to driveways is a must and the closing of streets to residents as well as businesses is out of the question;
- In well populated areas where water main breaks and rusty water plague the system;
- The water main runs underneath a bridge or overpass rendering access to the main impossible.

BASICS INSTALLATION STEPS

01. TEMPORARY BYPASS

Install temporary bypass through water meters or garden spigots

02. EXCAVATION

Excavate access pits at each end of the pipe section

03. CLEANING

Clean pipe with metal chain reamer

04. INSPECTION

Inspect pipe through closed-circuit television (CCTV) inspection to map the service connections

05. INSERTION

Insert plug in every service connection from inside the pipe using specialized robotic equipment

06. INJECTION

Inject epoxy into the liner on-site and pull into place

07. LINER FORMATION

Form the liner by sending swabs from one end to the other

08. CURING

Circulate hot water for curing

09. PRESSURE TEST

Perform hydrostatic pressure test

10. REINSTATE SERVICE

Reinstate service connections from inside the pipe by drilling using specialized robotic equipment

11. DISINFECTION AND RECONNECTION

Disinfect the pipe, test, and reconnect water distribution system

12. RESTORATION

Remove temporary bypass and restore site



Clean water main



Insert Al TRA



Robotically reinstating services

CERTIFICATIONS

- · Certified by NSF and UL to NSF/ANSI Standard 61
- Mechanical properties exceed ASTM F1216 and ASTM F1743 Standards
- Designated Class IV fully structural liner as per the AWWA M28 manual
- Meets the Solar Impulse Standards on Sustainability & Profitability
- Tested in compliance with Australian/New Zealand Standard 4020
- Standard BNQ 3660-950 approved product















